SUPERLOCK BOLT-ON INTERLOCKING KEEP

Specification Sheet

BSKS

FEATURES

- Maximum security: Prevents the gate from being levered or forced apart.
- Effortless installation: Simple to fit and suitable for a variety of applications.
- Smart look: Slim design enhances the gate's appearance for a clean, professional finish.
- Slim keep that fits between the gate and the post for use with the Superlock range of locks.
- The Superlock keep and Superlock gapless keep are also available for the Superlock range of locks.



PRODUCT DETAILS


Product code	Description
BSKS	Superlock interlocking secure keep

INCLUDED IN THE BOX

- Self expanding fixings for post bracket
- Expanding fastener



Expanding fastener



INSTALLATION

1. Drill 2 x 15mm (5/8") holes at 140mm (5 1/2") centres in the gate post for 2x expanding fasteners.
2. Insert expanding fasteners through the post bracket into the post, and tighten with 5mm hex key.
3. Drill 2x 9mm (3/8") holes at 140mm (5 1/2") centres in the gate (these will have already been drilled when fitting with a Superlock) and bolt the bracket on using the M8 fixing bolts supplied with the lock.

Caution: if using with double gates, ensure drop bolts are used and only one gate is opened at a time.

© Copyright Gatemaster 2026